



### **Dimensions of Cylinders**

<b>S.N.</b>	<b>Parameters</b>	<b>Capability</b>
1	Diameter of cylinder 'D' (mm)	Min 400 – Max. 1250
2	Scarffing Length (mm)	Min 40 min- Max 120 .
3	Height of Cylinder- H (mm)	Max.2100
4	Thickness S (mm)	1.50 – 6.00

### **Tolerances of Cylinders**

<b>S.N.</b>	<b>Parameters</b>	<b>Tolerance</b>
1	Diameter of cylinder 'D' (mm)	$\pm 10$ mm
2	Scarffing Length (mm)	$\pm 10$ mm
3	Height of Cylinder- H (mm)	+5 mm, - 2 mm
4	Thickness S (mm)	$\pm 10$ %



### Dimensions & Tolerances for Washers

S.N.	Parameters	Capability
1	Outer Diameter OD	Max 1800 mm
2	Inner Diameter ID	Min 150 mm
3	Thickness S	Up to 15 mm

S.N.	Parameters	Tolerance
1	Outer Diameter OD	$\pm 2$ mm
2	Inner Diameter ID	$\pm 2$ mm
3	Thickness S	$\pm 5\%$

### Dimensions & Tolerances for Phase Barriers

S.N.	Parameters	Capability
1	Length L	Min 750 mm-Max 2500 mm
2	Width B	Min 750 mm-Max 2500 mm
3	Thickness S	Up to 5 mm

S.N.	Parameters	Tolerance
1	Length L	$\pm 5$ mm
2	Width B	$\pm 5$ mm
3	Thickness S	$\pm 5\%$